

LM-W8ME

BUILT-IN MYQ WI-FI DC GARAGE DOOR OPENER SUITED FOR SECTIONAL GARAGE DOORS

Trusted reliability and quiet operation



KEY FEATURES

BUILT-IN MYQ WI-FI
for the easiest way to connect the garage.

LIFTING POWER
Powers Spring Balanced Sectional Doors Up To 150kg

SMART



MYQ CAPABLE TECHNOLOGY lets users create schedules, monitor, receive alerts and control the garage door opener away from home.¹



BUILT-IN MYQ WI-FI for the easiest way to connect the garage.



POWERFUL AND RELIABLE

DC MOTOR is purposefully designed for quiet performance

SOFT-START AND SOFT-STOP Smooth operation

AUTOMATIC STOP Open or Close travel and obstruction detection

STRONG AND QUIET RAIL Two steel/chain rail options.
7025CR3-W8ME for doors up to 2.5m high
7030CR3-W8ME for doors up to 3.0m high

2 YEAR WARRANTY Full 2 Year Product warranty for peace of mind

SECURE

TIMER-TO-CLOSE automatically closes the door after a preset amount of time

SECURITY+ 2.0® Transmitters communicate on multiple frequencies with encrypted rolling code. This ensures the strongest frequency is selected every time, virtually eliminating interference while providing the highest level of security

INCLUDED ACCESSORIES

SECURITY+ 2.0 PREMIUM REMOTE CONTROL

Each remote operates up to 4 garage door openers



ME960-LM

WIRED WALL CONTROL

Controls one garage door opener



75EW

POWERFUL ADD-ONS

PROTECTOR SYSTEM (Safety IR Beams)

The safety beams allow the door to auto-reverse if there is an obstruction.

IR Beams are required for myQ¹.



771ESA

WEATHER COVER (MOULDED)

This discreet, purpose designed cover protects the opener from weather conditions.



093A0963

¹ Additional purchase of IR Beams accessory required to enable built-in myQ Wi-Fi functionality.

LM-W8ME

DC GARAGE DOOR OPENER SUITED FOR SECTIONAL GARAGE DOORS WITH BUILT-IN MYQ WI-FI

MASTERFUL ENGINEERING

MOTOR



- 12V DC
- Automatic Thermal Protection
- Permanent Lubrication

POWER



- 220-240 AC
- 50-60 Hz

MECHANICS



- **Steel Chassis and Plastic Cover**
- **One Piece Chain Rail** available in two sizes to suit doors up to 2.5m or 3.0m in height.
- **Sprocket Drive Mechanism**
- **Auto-Force** Adjusts for changing conditions.
- **Electronic Limits** for easy setup



DIMENSIONS



- **Max. Door Size:** 3.0m high by 5.5m wide = 16.5m²
- **Max Spring Balanced Load:** 20kg
- **Headroom Clearance Required:** 230mm from center of torsion bar



MAX. DOOR WEIGHT
150kg

SAFETY AND SECURITY.

SAFETY

- Timer-To-Close/Unattended Close Operation¹
- Emergency/Quick Release
- Down Safety Reverse
- Up Safety Stop

¹ Note: to reduce the risk of injury to persons, only use Timer-To-Close/Unattended Close Operation features when installed with a sectional door. The IR Beams must be installed for Timer-To-Close

SECURITY

SECURITY+ 2.0®

- Radio Controls
- ME960-LM Remote Control: 433 MHz

SHIPPING.


SHIPPING WEIGHT

6.35kg

CARTON (1)

Opener carton and contents:
L 51.4cm x W 28.9cm x H 24.7 cm

- Garage Door Opener (LM-W8ME)
- 2x Security+ 2.0 Premium Remote Control (ME960-LM)
- 75EV Wired Push Button



LM-W8ME

DC GARAGE DOOR OPENER SUITED FOR SECTIONAL GARAGE DOORS WITH BUILT-IN MYQ WI-FI